1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY

<u>1.1 Trade name</u> NYLON

1.2 Use of the product 3D-Printer filament

1.3 Supplier Ultimaker (Watermolenweg 2 4191PN Geldermalsen The Netherlands)

Emergency phone number In case of toxicological emergency contact your physician

2. HAZARDS INDENTIFICATION ACCORDING TO 1272/2008/EC

2.1 Classification of the substance or mixture

No risk exists to the health of users if the product is handled and

processed properly

2.2 Label elements

Labelling (Regulation 1272/2008/EC) Not applicable

2.3 Other hazards Not known

3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Composition Polyamide

3.2 Mixture Polyamide, additives (wax and/or dyes) and spinfinish

4. FIRST AID MEASURES

4.1 Description of first aid measures General advice: If you feel unwell, seek medical advice (show

the label where possible). Never give anything by mouth to an

unconscious person

In case of inhalation of gases released from molten filament,

move person into fresh air

Skin contact Wash with soap and water. Seek medical attention if symptoms

occur. If burned by contact with hot material, cool molten material adhering to skin as quickly as possible with water, do not try to peel it off and seek for medical attention, if necessary,

for removal and treatment of the burns

Eye contact Any material that contacts the eye should be washed out

immediately with water. If easy to do, remove contact lenses. Seek medical attention if symptoms persist. If molten material contacts the eye, immediately flush with plenty of water for at

least 15 minutes. Seek medical attention immediately

Ingestion Not probable. Seek medical advice in case ingestion occurs

Note to physician Treat symptomatically

<u>4.2 Most important symptoms</u> Burns should be treated as thermal burns. The material will

come off as healing occurs; therefore immediate removal from

skin is not necessary

4.3 Indication of any immediate medical attention and special treatment needed

and effects, both acute and delayed

No data available

5. FIREFIGHTING MEASURES

Material can accumulate static charges which may cause an electrical spark (ignition source). Use proper bonding and/or

grounding procedures

5.1 Extinguishing media Foam, carbon dioxide (CO₂), water or dry chemical.

Unsuitable extinguishing media: not known

5.2 Special hazards arising from the substance or mixture

Burning produces obnoxious and toxic fumes: aldehydes,

carbon oxides (CO)

5.3 Advice for firefighters Use self-contained breathing apparatus and full protective

clothing

6. ACCIDENTAL RELEASE MEASURES

<u>6.1 Personal precautions, protective</u> equipment and emergency procedures

Avoid breathing gases released from molten filament. Ensure adequate ventilation, especially in confined areas

6.2 Environmental precautions No data available

<u>6.3 Methods and materials</u> for containment and cleaning up Allow molten material to solidify. Dispose of waste and residue

according to local regulations

6.4 Reference to other sections

7. HANDLING AND STORAGE

7.1 Precautions for safe handling Avoid contact with molten material

7.2 Conditions for safe storage, including any incompatibilities

Product should be stored in a dry and cool place at temperatures between -20 to +30 °C. Avoid direct sunlight. Minimize moisture uptake by leaving it in a sealed package

together with the supplied dessicant

7.3 Specific end use(s) Filament for 3D printing

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters None

DNEL: No data available

PNEC: No data available

8.2 Exposure controls

Eye protection Use safety glasses for prolongated stare at printing

Skin and body protection Good practices suggest to minimize skin contact. When

material is heated, wear gloves to protect against thermal burns

Respiratory protection If engineering controls do not maintain airborne concentrations

below recommended exposure limits (when applicable) or to an acceptable level (in countries where exposure limits have not been established) an approved respirator must be worn. Respirator type: air-purifying respirator with an appropriate government approved (where applicable) air purifying filter, cartridge or canister. Contact a health and safety professional

or manufacturer for specific information

Hand protection Follow good industrial hygiene practices

Hygiene measures Follow good industrial hygiene practices

Engineering measures Good general ventilation (typically 10 air changes per hour)

is recommended. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation or other engineering controls that maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an

acceptable level

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance Filament

Color Transparent and black

Odor Slight
Flash point > 400 °C

Ignition temperature -

Thermal decomposition > 300 °C
Auto-ignition temperature > 430 °C
Melting point/range 185 - 195 °C
Density 1.14 g/cm³
Water solubility Insoluble

Solubility in other solvents Sulfuric acid, 96%

9.2 Other information -

10. STABILITY Stable under recommended storage conditions

10.1 Reactivity No data available

10.2 Chemical stability Good chemical stability

10.3 Possibility of hazardous reactions No decomposition or hazardous reactions if stored and applied

as directed

10.4 Conditions to avoid Print temperatures above 280 °C (at standard printing speeds)

10.5 Incompatible materials -

<u>10.6 Hazardous decomposition products</u> See 5.2

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Principle routes of exposure Eye contact, skin contact, inhalation, ingestion

Acute toxicity There were no target organ effects noted following ingestion or

dermal exposure in animal studies

Skin corrosion/irritation May cause eye/skin irritation. Product dust may be irritating to

eyes, skin and respiratory system

Reproductive toxicity

No data available

Carcinogenicity No data available

12. ECOLOGICAL INFORMATION

12.1 Toxicity

To date, proper use of the monofilament has not been

associated with any detrimental effect on health

12.2 Persistence and degradability Non-degradable

12.3 Bio accumulative potential Bio accumulate

12.4 Mobility in soil Product is solid, remove or recycle according to local and

national regulations

12.5 Results of PBT and vPvB assessment No data available

12.6 Other adverse effects Not known

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods In accordance with local and national regulations

14. TRANSPORT INFORMATION

ADR Not regulated RID Not regulated IATA Not regulated IMDG Not regulated Not regulated Not regulated Not regulated Not regulated Not regulated

Special precautions for user -

15. REGULATORY INFORMATION

Not meant to be all inclusive - selected regulations represented

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

US Regulations:

Sara 313 title III TSCA Inventory List OSHA hazard category CERCLA WHMIS -

State right-to-know requirements

Other Inventories:

Canada DSL Inventory List -

REACH/EU EINIECS Components are in compliance with REACH

NEHAPS Japan (ECL/MITI) Australia (AICS) Korean chemical inventory Philippines (PICCS) inventory Chinese Chemical Inventory (IECSC) -

15.2 Chemical Safety Assessment -

16. OTHER INFORMATION

The information provided in this Safety Data Sheet (SDS) is based on current knowledge and experience. This information is provided without warranty. This information should help to make an independent determination of the methods to ensure proper and safe use and disposal of the filament

VERSION Version 2.001

DATE 09/08/2016